

REVISION		RECORD	
REV.	CONTBNT	MOD.	DATE

2P-双卡点

5.08*P

5.80

- 5. Using Temperature Range:-40° C - +105° C
- 6. Suitable Electric Wire: 28-12AWG
- 7. Screw Torque Value: 0.5 N.m

2P-左单卡点

15.00

7. 螺丝扭力: 0.5 N.m

	pitch dimension			Nominal dimension					Symbol
	over 0	over 6	over 10	over 0	over 30	over 60	over 100	over 150	
variable range	to 6	to 10	to 24	to 30	to 60	to 100	to 150		
Tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7	±1.0	

3.	LC1-5.08-夹子	L001B0001AY	P	磷青铜	镀锌
4.	LC1-5.08-侧夹块	PIA0HLCS003V	P	黄铜	镀锌
1.	LC1-5.08-螺丝	SP0YA305302V	P	碳钢	三价铬钝化彩锌
2.	PT1-5.08-盖子	1130C0YXXAY	1	PA66	
1.	PT1-5.08-主体	1130A0YXXAY	1	PA66	
NO.	NAME OF PART	NO. OF PART	Q'TY	MATERIAL	NOTES
DRS.	LDD	DATE	2015/01/08	UNITS	MM
CHK.		DATE		SIZE	A4
APP.		DATE		SCALE	1:1

上海联捷电气有限公司
Shanghai Elinkor Electric C.O,LTD

TITLE
PT1-5.08-XP-1Y-0
PT1-5.08-成品