



REVISION RECORD			
REV.	CONTENT	MOD.	DATE
①	焊脚宽度变更	LDD	14/04/08

技术要求:  
 间距: 10.16mm  
 额定电压: 1000V  
 额定电流: 57A  
 耐电压值: AC3500V/1min  
 绝缘阻抗: 5000MΩ/DC1000V  
 使用条件: -40℃~+105℃  
 适用线规: 20~6 AWG  
 螺丝扭矩: 1.2N.m

NOTES:  
 Pitch: 10.16mm  
 Rated Voltage: 1000V  
 Rated Current: 57A  
 Withstand Voltage:  
 AC3500V for 1 minute  
 Insulation Resistance:  
 5000MΩ / DC1000V  
 Using Temperature Range:  
 -40℃ ~ +105℃  
 Wire range :20 ~6 AWG  
 Screw Torque Value : 1.2N.m

10.16

TOLERANCE										DESIGN		DATE		SCALE		DWG NO.		TITLE		
range	to	to	to	to	to	to	to	to	to	APP.	DATE	SCALE	1:1	DWG NO.	SP-1-2070A01	REV: Y1				
	6	10	24	30	60	100	150			上海联捷电气有限公司										
tolerance	±0.1	±0.15	±0.25	±0.2	±0.3	±0.5	±0.7			LG1016B-10.16-XP-1P-00A										